GROMMETS

Facility Monitoring

SPLIT INTEGRAL FOAM GROMMETS ROUND, SQUARE, AND RECTANGLE

APPLICATIONS: Plugging holes is one of the easiest ways to improve airflow and efficiency in any raised floor environment. If air can escape through holes in a raised floor you limit the effectiveness of containment and decrease your cooling efficiency.

RLE's patented fire rated foam grommets seal holes in raised floors and show an immediate efficiency return.

(1) KEY FEATURES:

- Foam composition seals better and lets less air escape than the leading competitor
- Split design is easy to insert around any size cable bundle in existing cutouts
- Fulfills best practice guidelines for data center containment scenarios
- Available in a variety of sizes to meet a wide range of needs
- Flame rated to meet facility safety requirements
- 4 screws provided to ensure a secure installation

03

WHAT SETS RLE'S GROMMETS APART?

- Our foam grommets seal better and prevent air from passing through the grommets significantly better than the leading competitor's grommets.
- Purchase one or several grommets at a time - we understand each facility's needs are unique, and want to help you meet your individual efficiency goals. Whether you need one grommet or a box full, we're happy to help.
- Use whole or quickly split into halves for installation around existing cables or pipes, or against a flat edge.
- Shipped in the USA, our grommets are stocked and ship from our manufacturing facility in Colorado.
- Our patented design is a testament to our commitment to innovation and ensures you receive the quality and reliability you expect from all RLE products.

https://parametersystems.com

970-232-3946

Sales@rletech.com

V09.24



GROMMETS DATASHEET Page 2

04

50% LESS AIRFLOW LOSS THAN THE LEADING COMPETITOR: Fill cutouts in raised floors with RLE's grommets and see an immediate improvement in airflow and efficiency.



05

GROMMETS: Compatible with all new and existing raised floor systems

Product Codes				
GRM-6RND	Grommet; round; 6" (15.24 cm)			
GRM-6X4	Grommet; rectangular; 6" x 4" (10.16 x 15.24 cm)			
GRM-6X6	Grommet; square; 6" x 6" (15.24 x 15.24 cm)			
GRM-6X9	Grommet; rectangular; 6" x 9" (15.24 x 22.86 cm)			

06

How Much Better Are RLE's Grommets? Our grommets were tested against the leading competitor's grommets. The results tell the story:							
Test - Using an air hood, what is the measured plenum pressure in each situation?	Competitor's 6" Round Grommet (CFM/100 in ²)	RLE's 6" Round Grommet (CFM/100 in ²)	How much less air escapes when you use RLE's grommet instead of the competitor's? Improvement calculated in percentage of airflow.	Estimated Savings Per Year with RLE Grommets, per 100 in ²			
No Cable Bundle	5.656	2.502	55.76%	\$73.60			
Small Cable Bundle	6.779	2.812	58.52%	\$77.24			
Medium Cable Bundle	8.032	4.430	44.85%	\$59.20			
Large Cable Bundle	10.200	5.422	46.84%	\$61.83			

https://parametersystems.com


970-232-3946

Sales@rletech.com

V09.24



06



07

Technical Specifications							
Product Code	GRM-6RND	GRM-6X4	GRM-6X6	GRM-6X9			
Overall Size	7.5" x 1.75" (19.05cm x 4.45cm)	7.84" x 5.87" x 1.75" (19.91cm x 14.91cm x 4.45cm)	7.84" x 7.84" x 1.75" (19.91cm x 19.91cm x 4.45cm)	7.79" x 10.74" x 1.75" (19.79cm x 27.28cm x 4.45cm)			
Weight	7.4oz (210g)	6.5oz (184g)	9.5oz (270g)	12.5oz (346g)			
Height Above Floor	0.25" (0.635cm)	0.25" (0.635cm)	0.25" (0.635cm)	0.25" (0.635cm)			
Hole Cut Diameter Minimum Maximum	6.0" (15.24cm) 5.78" (14.68cm) 6.22" (15.8cm)	6.0" x 4.0" (15.24cm x 10.16cm) 5.84" x 3.88" (14.83cm x 9.86cm) 6.10" x 4.13" (15.49cm x 10.49cm)	6.0" x 6.0" (15.24cm x 15.24cm) 5.84" x 5.84" (14.83cm x 14.83cm) 6.10" x 6.10" (15.49cm x 15.49cm)	6.0" x 9.0" (15.24cm x 22.86cm) 5.84" x 8.80" (14.83cm x 22.35cm) 6.50" x 9.50" (15.49cm x 24.13cm			
Usable Cable Area	15.9 in2 (102.6 cm2)	11.8in2 (76.1cm2)	20.8in2 (134.2cm2)	34.2in2 (220.6cm2)			
Composition Frame Foam	Polypropylene Ensolite SFO						
Flame Rating Frame Foam	UL94 H-B UL94 HF-1						
Compatibility	Compatible with all new and existing raised floor systems						
Country of Origin	United States of America						

https://parametersystems.com

970-232-3946

Sales@rletech.com

V09.24

