

LDCE

Leak Detection

CABLE EVALUATOR

01 APPLICATIONS: If you have used our cableconnector construction tools to build your own sensing cables or to re-install mating cable connectors, use the LDCE to test the cable for accuracy and quality before installing it in a leak detection system.

02 KEY FEATURES:

- Quality construction verified to work with RLE cables
- The only cable tester recommended by RLE

03 WHAT SETS RLE'S LDCE APART?

- **The same quality tools used by our manufacturing staff.** All SeaHawk cables are fully tested before they leave our manufacturing facility. The LDCE replicates this testing process, verifying the cables you built were assembled correctly.
- **Isolate a problem within a larger system.** The LDCE simplifies cable testing, system troubleshooting, and maintenance because it measures leakage current across the cable's two sensing wires. Testing your cable is important because a high leakage current can affect the accuracy of readings.

04 VERIFY YOUR SENSING CABLES: Test and measure the precision of any length of sensing cable.



05 LDCE: For use with SC and SC-ZH

Product Codes

Product Codes	Cable evaluator; multimeter not included; for use with SC and SC-ZH
----------------------	---

06 LDCE Technical Specifications

Power	Cable evaluator; multimeter not included; for use with SC and SC-ZH
Sensing Cable Input	Supplied with 2ft (0.61m) interface cable; interface cable is pre-connected
Output Jacks	1 Red (Voltage); 1 Black (Common); and 1 Blue (Current)
Front Panel Interface Push Buttons	One Cable Test; One System Check
Operating Environment Temperature Humidity Altitude	32° to 122°F (0° to 50°C) 5% to 95% RH, non-condensing 15,000ft (4,572m) max.
Storage Environment	-4° to 158°F (-20° to 70°C)
Dimensions	4.4"L x 2.5"W x 1.5"H (11.2cmL x 6.4cmW x 3.8cmH)
Weight	0.5 lbs (0.226 kg)
Certifications	RoHS compliant